

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1) (Original) A method for separating constituents of a feed in liquid solution of at least two constituents (A, B) of different partition coefficients such that they are carried along at unequal velocities respectively by a light solvent and by a heavier solvent, in a device comprising at least one liquid-liquid centrifugal chromatographic column (col) consisting of the interconnection in series of at least one set of separation cells (CE), characterized in that it comprises:

- injecting the feed at an intermediate point of said set of cells, and
- carrying out alternating cycles of two stages, with a first stage during a first time interval (t_1) wherein a lighter solvent is injected through a first end of the device and a first constituent is collected at a second end of the device, and a second stage during a second time interval (t_2) wherein a heavier solvent is injected through the second end of the device and a second constituent is collected at the first end.

2) (Original) A method as claimed in claim 1, wherein the respective durations (t_1 , t_2) of the first and second phase and/or the lighter and heavier solvent injection rates are adjusted according to the constituents of the mixture, so as to obtain optimum separation.

3) (Currently Amended) A method as claimed in claim 1 ~~or 2~~, wherein several

cascade separations are performed to isolate from one another the various constituents of a mixture comprising more than two constituents.

4) (Original) A method as claimed in claim 3, wherein two optical isomers are separated by injecting into a first device a feed comprising the optical isomers and a chiral selector so as to obtain a first isomer on the one hand and a mixture of second isomer and of chiral selector on the other hand, and by injecting said mixture from the first device into a second device suited to separate the second isomer and the chiral selector.

5) (Currently Amended) A method as claimed in ~~any one of the previous~~ claims claim 1, wherein the feed is injected continuously or discontinuously.

6) (Original) A device for continuous separation of the constituents of a feed in liquid solution of at least two constituents (A, B) having different partition coefficients such that they are carried along at unequal velocities respectively by a lighter solvent and a heavier solvent, comprising at least one liquid-liquid centrifugal chromatographic column (col) consisting of the interconnection in series of at least one chain of separation cells (CE), characterized in that each column is associated with a first pump (P1) for injecting the feed at an intermediate point of the chain of cells, a first valve (V1) connecting a first end of the column to a first vessel for collecting a first constituent (FA) or to a second pump (P2) for injecting a first solvent (L), a second valve (V2) connecting a second end of the column to a second vessel for collecting a second constituent (FB) or to a third pump (P3) for injecting a second solvent (1), alternating valves (V1, V2) switching means so as to switch alternately from a first stage with

injection of the first solvent (L) and reception of the separated second constituent (FB) to a second stage with injection of the second solvent (1) and reception of the separated first constituent (FA), and means for controlling the pump flow rate.

7) (Original) A device as claimed in claim 6, comprising at least two cascade separation columns for separating constituents of a mixture comprising at least three different constituents.